JIVANJOR Jubiguard DRIPSHIELD Anti-Corrosive Integral Liquid Waterproofing Compound

JUBIGUARD DRIPSHIELD is a specially formulated integral waterproofing admixture compound for concrete/mortar. It chemically converts water-soluble compounds into stable equivalents, providing excellent plasticizing properties, enhancing cohesion, and preventing segregation. Ideal for all types of concrete, mortar, and plaster projects requiring water impermeability and reduced cracks.

Meets the requirement of IS:2645-2003

Application Areas

Waterproofing of concrete and sand-cement mortars used in

· Basements,

įC

- Roof Slabs and Screeds,
- Water Tanks & Water Retaining Structures,
- External Plastering,
- Bathrooms and Balconies,
- Sumps and Drains

Technical Details

Properties	Values	Test Standards
Colour	Brown	-
Form	Liquid	-
Density	1.00 ± 0.05g/cc	ASTM D 1475-98
Solid Content	10 ± 2%	ASTM D 1644-01
Chloride Content	0.02%	IS:2645-1975
Flash Point	>100°C	ASTM D 93
Initial Setting Time	175 mins	ASTM C191-82
Final Setting Time	255 mins	ASTM C191-82



- 200 ml per 50 kg bag of cement for concrete mortar mix
- 150 ml per 50 Kg bag of cement for plaster mortar mix








INTEGRAL WATERPROOFING COMPOUND

JUB

JUBILANT

_____ Pack Sizes _____ 200 ml, 1 ltr, 5 ltr, 10 ltr & 20 ltr




Precautions & Limitations

- Do not add JUBIGUARD DRIPSHIELD directly to dry cement & aggregate mix.
- · Maintain water-cement ratio as low as possible.

I and, therefore, entirely your own responsibility

• Do not increase the dosage of JUBIGUARD DRIPSHIELD than the recommendation.



Version No. VN01/04/2024. Please note that this datasheet supersedes all previous versions

For professional use only. Keep out of reach of children. This Information and our technical advice - whether verbal, in writing, or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use, and processing of our products manufactured by you on the basis of our technical advice - selecially that contained in the basis of our technical advice are beyond our

For Feedback/complaints, write to Product Manager, CPD, Jubilant Agri and Consumer Products Limited Plot No. 142, Chimes, 3rd Floor, Sector 44, Gurugram 122003, Haryana, India Tel.: +91 120 6290100 E-mail: jivanjor@jubl.com Website: jacpl.co.in